



Note :

Pin 1 : Right

Pin 2 : Top

Pin 3 : Left

Pin 4 : Bottom

Pin Pitch : 1.0 mm

ITO Glass : 0.7 mm

Total Thickness : 1.0 ±0.1 mm

| | | | | | | | |
|----|-------------|----|-------|---|----------------------|-------|----------------|
| 品名 | SE-AC8265-2 | 製圖 | Jason | 良英股份有限公司 SUPER ELITE TECHNOLOGY CO., LTD | 單位 : mm 公差 : 一般公差 | 發行日期: | 10 - 24 - 2003 |
| | | 確認 | Cheng | | | 變更日期: | |

Touch Panel Specification

SET

Page

2/2

1. Suitability

This specification suit analog resistance touch panel. which used in LCD module.

2. Apply To Specification

2.1.Surface Hardness : 3H ↑

2.2. Optical Clarity : 80 % ↑

2.3 Operating Temperature : -10°C ~ 60°C

2.4 Storage Temperature : -20°C ~ 70°C

2.5 Operating Voltage : DC5V

2.6 Operating Current : 5mA ~ 25mA

2.7 Isolation Resistance : 20MΩ ↑ @DC25V

2.8 Linearity : ±1.5% ↓

2.9 Operation Pressure : 25 ~ 50g

2.10 Resistance : 200Ω ~ 900Ω

2.11 Faceplate Surface : glare coating