



Note :

V/A : VIEW AERA

A/A : ACTIVE AERA

Pin 5 : LT

Pin 4 : RT

Pin 3 : AD-X

Pin 2 : RB

Pin 1 : LB

Pin Pitch : 2.54 mm

ITO Glass : 1.8 mm

Total Thickness : 2.1 ± 0.2 mm

Resistance : 20Ω ~300Ω

Linearity : < 1.5%

Faceplate Surface : Anti-glare coating

品名	SE-5W1711-1	製圖	Angus	良英股份有限公司 SUPER ELITE TECHNOLOGY CO., LTD	頁次 : 1/1	發行日期	04- 22 - 2002
		確認	Jason			變更日期	10- 17 - 2005

Touch Panel Specification

SET

Page

2/2

1. Suitability

This specification suit analog resistance touch panel. which used in CRT module.

2. Apply To Specification

2.1.Surface Hardness : 3H ↑

2.2. Optical Clarity : 78 ~ 82 %

2.3 Operating Temperature : -10°C ~ 60°C

2.4 Storage Temperature : -20°C ~ 70°C

2.5 Operating Voltage : DC5V

2.6 Faceplate Surface : Anti-glare coating

2.7 Isolation Resistance : 20MΩ ↑ @DC25V

2.8 Linearity : ±1.5% ↓

2.9 Operation Pressure : 100g ↓

2.10 Resistance : 20Ω ~ 100Ω